



CUMI SHARP



WHITE FUSED ALUMINA

White Fused Aluminium oxide grains is a high purity medium density product manufactured in electric arc furnace from a controlled quality of pure grade Bayer Alumina. It is more friable than regular Brown grade produced from Bauxite.

APPLICATION

CUMI SHARP White Fused Aluminium oxide grains used in ferrite manufacturing industry mainly as a bedding material on the ovens where ferrites are heat treated.

GRAIN SIZES AVAILABLE

12, 14, 16, 20, 24, 30, 36, 40, 46, 54, 60, 70, 80, 80, 90, 100, 120, 150, 180 and 220 as per FEPA (Federation of European Producers of Abrasives) standard 42-1:2006.

TYPICAL PROPERTIES

Physical Properties		
Property	Unit	Value
Hardness	Mohs Scale	9
Hardness	Knoop Scale (Kg/mm ²)	2150
Specific gravity		3.8

Chemical composition	
Constituent	Value *
Al ₂ O ₃	99.52 %
TiO ₂	0.03 %
SiO ₂	0.02 %
Fe ₂ O ₃	0.03 %
Na ₂ O	0.38 %

* Analyzed for Grit F 24

Packing: 25 kg multiply paper bags of 1000 kg palletized. Other packaging types on request

General Inquiries:-
salesemd@cumi.murugappa.com
info@cumi-emd.eu
www.cumi-emd.eu

Alumina Plant:-
CARBORUNDUM UNIVERSAL LIMITED
Electro Minerals Division
P.B.No.1, Kalamassery Development Plot PO
Kochi - 683 109, India
Tel.: +91 484 2540799; Fax: +91 484 2532019
salesemd@cumi.murugappa.com

SiC Plant:-
CARBORUNDUM UNIVERSAL LIMITED
Electro Minerals Division
P.B.No.3, Nalukettu
Koratty - 680 308, India
Tel.: +91 480 2732313; Fax: +91 484 2732821
salesemd@cumi.murugappa.com

Europe Contact:-
Schmiedegasse 24
D-50735 Köln, Germany
Tel.: +49 (0)151 1274 0882
Fax: +49 (0)221 2714 0047
info@cumi-emd.eu